

KVK SILENT 355 EC

Item no. 92173

Document type: **Product card**
Document date: **2019-07-10**
Generated by: **Systemair Online Catalogue**



Description

- Low sound level, thick and high density insulation
- Compact design, easy installation
- Easy maintenance, service cover
- Air tight design
- High efficiency and low SFP in a real working point
- Potentiometer included, possible to speed control 0-100%
- Simple to install, mounting brackets included
- Integrated motor protection
- Aluzinc casing, C4 corrosion class

KVK Silent is a box fan with circular duct connections. The casing is insulated with thick and high density mineral wool insulation. The casing is manufactured from Aluzinc in corrosion class C4.

KVK Silent EC is delivered with integrated motor protection and pre-wired potentiometer (0-10V) that allows you to easily find the desired working point. The fan can be demand controlled via sensors for CO₂, temperature, humidity, presence indication and VAV. Size 315-500 also offers possibility to communication via Modbus.

KVK Silent can be installed in any position.

The FK mounting clamp (accessory) facilitates easy installation and removal and prevents the transfer of vibration to the duct.




Technical parameters

Nominal data		
Voltage	230	V
Frequency	50/60	Hz
Phase	1	~
Input power (P1)	533	W
Current	2,36	A
Max. airflow	1	m ³ /s
R.p.m.	1803	r.p.m.
Weight	64	kg
Temperature data		
Max. temperature of transported air	60	°C
Max. temperature of transported air when speed-controlled	60	°C
Sound data		
Sound pressure level at 3 m	53,3	dB(A)
Protection / Classification		
Insulation class	F	
Enclosure class, motor	IP55	

Diagrams


Diagrams



Max efficiency


Hydraulic data										
▲ Working air flow		0,601 m³/s								
▲ Working static pressure		363 Pa								
▲ Power		520 W								
Speed		1832 r.p.m.								
Current		2,27 A								
SFP		0,864 W/(l/s)								
Voltage		230 V								
Sound power level		63	125	250	500	1k	2k	4k	8k	Tot
Inlet	dB(A)	61	70	69	57	55	55	52	45	73
Outlet	dB(A)	55	68	71	66	68	63	57	48	75
Surrounding	dB(A)	42	52	60	49	42	39	31	32	61

Dimensions



KVK SILENT	A	B	C	D	E	øF	G
355 EC	1041	922	852	748	538	355	1045

Wiring



RD	Red
YE	Yellow
BU	Blue
WH	White
GN	Green
BN	Brown
BK	Black

Accessories

Electric accessories

[RT 0-30 Room Thermostat \(5151\)](#)
[CO2RT-R-D Transmitter \(6993\)](#)
[Presence detector/IR24-P \(6995\)](#)
[MTV-1/010 Controller 0..10V+ \(30650\)](#)
[DMD-C Pressure controller \(15793\)](#)
[MTP 10, 10K, Speed control \(32731\)](#)
[EC-Vent Room Unit \(3018\)](#)
[EC-Vent control board \(3115\)](#)
[REV-3POL/03 ON/OFF \(33978\)](#)
[MTP 20, on/off, 3-step \(310220\)](#)
[EC-Basic-H humidity \(24807\)](#)
[EC-Basic-T temperature \(24805\)](#)
[EC-Basic-U universal 0-10V \(24806\)](#)
[EC-Basic-CO2 and temperature \(24808\)](#)
[EC-Selector \(9908\)](#)
[CXE/AVC Modbus \(37256\)](#)
[S-5EC/FRQ \(76738\)](#)
[PCA 1000D2 Pressure controller \(76739\)](#)

Accessories

[CB 355-9.0 400V/3 Duct heater \(5389\)](#)
[CB 355-12.0 400V/3 Duct heater \(5390\)](#)
[CBM 355-9.0 400V/3 Duct heater \(5486\)](#)
[LDC 355-900 Silencer \(5399\)](#)
[FFR 355 Filter cassette \(1782\)](#)
[FGR 355 Filter cassette \(1821\)](#)
[FK 355 Fast clamp \(1614\)](#)
[SG 355 Protection guard \(5612\)](#)
[VK-35 Louvre shutter \(5642\)](#)
[RSK-355 Back draft dmp. \(9972\)](#)
[CB 355-6.0 400V/2 Duct heater \(5388\)](#)

Documentation



KVK_Silent_Slim_Operating_maintenance_145899_CE_EN_A007.pdf (1,47MB)



MODBUS LITE V5.01 parameter specification.pdf (726,08kB)